

SERVOCUT 302 MA Troncatrice Abrasiva Automatica



Model	302-MA	302-MA-AX	302-MA-MX
Max. Wheel Diameter	Ø300 mm	Ø300 mm	Ø300 mm
Max. Cutting Capacity, Ø	Ø110 mm	Ø110 mm	Ø110 mm
Max. Cutting Capacity, HxD	#70×200 mm	#70×200 mm	#70×200 mm
Z-Axis Travel, (mm)	125	125	125
Y-Axis Travel, (mm)	220	220	220
X-Axis Travel, (mm)	–	95	95
T-Table Dimension, (mm)	444×275	(395+95)×275	(395+95)×275
T-Slot Dimension, (mm)	12 mm	12 mm	12 mm
Cutting Motor Power (S1)	4 kW	4 kW	4 kW
Wheel Speed, RPM	600-4000	600-4000	600-4000
Cutting Feedrate, (µm/s)	20-5000	20-5000	20-5000
HMI Touch Screen	7 inch	7 inch	7 inch
Chop Cutting, Z- Axis	Manual	Manual	Manual
Table Feed Cutting, Y- Axis	Auto	Auto	Auto
Parallel Cutting, X-Axis	–	Auto	Manual
Table Oscillating Cutting	–	–	–

Table Oscillating Cutting	–	–	–
Rapid Pulse Cutting	Standard	Standard	Standard
Smart Feed Control	Standard	Standard	Standard
StepCut; SegmentCut; DiagonalCut	–	–	–
Size WxDxH, (cm)	94x99x76	94x99x76	94x99x76
Weight	250 kgs	250 kgs	250 kgs
Recirculation Cooling Unit	80 lt	80 lt	80 lt