

SERVOCUT 502 Troncatrice Automatica e Motorizzata



Model	502	502-AX
Max. Cut-off Wheel Diameter	Ø500 mm	Ø500 mm
Max. Cutting Capacity, Ø	Ø180 mm	Ø180 mm
Max. Cutting Capacity, HxD	100×400 mm	100×400 mm
Z-Axis Travel, (mm)	350 mm	350 mm
Y-Axis Travel, (mm)	380 mm	380 mm
X-Axis Travel, (mm)	–	200 mm
T-Table Dimension, (mm)	764×608	(634+200)×608
T-Slot dimension, (mm)	12 mm	12 mm
Cutting Motor Power (S1)	11 kW	11 kW
Variable Wheel Speed	600-2400 RPM	600-2400 RPM
Cutting Feedrate, (µm/s)	20-5000 µm/s	20-5000 µm/s
HMI Touch Screen Controller	7 inch	7 inch
Chop Cutting in Z- Axis	Auto	Auto
Table Feed Cutting in Y-Axis	Auto	Auto
Parallel Cutting in X-axis	–	Standard
Table Oscillating Cutting	Standard	Standard
Rapid Pulse Cutting	Standard	Standard
Smart Feed Control	Standard	Standard
StepCut; SegmentCut; Diagonal-Cut	Optional	Optional
Automatic Cleaning System	Optional	Optional
Size WxDxH (cm)	140x134x185	140x134x185
Weight	1100 kgs	1100 kgs
Recirculation Cooling Unit	135 lt	135 lt